



AT TOP AND BOTTOM
ANCHOR WRAP
TWISTED WIRE
BACK ON ITSELF
MIN. 3 FULL TURNS

.084" DIA. TYPE 304
STAINLESS STEEL TWISTED
WIRE "TYLE-TYE"

.090 DIA. TYPE 304
STAINLESS STEEL 3"
WIND LOCKS TYP.

16" EXPOSURE

19" TILE

13" EXPOSURE

BOOSTER TILE

BIRD STOP

11"

TYP. GALV. STEEL "WOOD DECK ANCHOR"
SCREWED TO METAL "z" SECTION USING
TWO (2) TWO 1/4"x1-1/4" SELF TAPPING
ZINC - PLATED SCREWS PER ANCHOR.
ANCHOR SPACING NOT TO EXCEED 4 FEET
O.C. ALL TABS SEALED WITH MASTIC.

.0625 DIA. TYPE 304 18" TIE WIRE TO
BE WRAPPED AROUND ITSELF 3 FULL
REVOLUTIONS AT EACH JUNCTION -
TYP. FOR ALL TILES.

8" STRAIGHT BARREL MISSION "TYLE-TYE" FIELD DETAIL

MCA - 8" STRAIGHT - MTL - 3D
N.T.S.